

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT

(10) International Publication-Number
WO 2004/059568 A1

(51) International Patent Classification?: **G06K 9/00**,
H04N 7/18, A61B 1/04, 1/06

Zvika [IL/IL]; 19 Moshe Sne, Hod Hacarmel, 34987 Haifa (IL).

(21) International Application Number:
PCT/IL2003/001105

(74) Agents: EITAN, PEARL, LATZER & CO-
HEN-ZEDEK et al.; 2 Gav Yam Center, 7 Shenkar
Street, 46725 Herzlia (IL).

(22) International Filing Date:
25 December 2003 (25.12.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/436,004 26 December 2002 (26.12.2002) US

(71) Applicant (for all designated States except US): GIVEN
IMAGING LTD. [IL/IL]; P.O.B 258, 20692 Yoqneam Ilite
(IL).


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): IDAN, Gavriel J.
[IL/IL]; 44A Einstein Street, 34602 Haifa (IL). GILAD,

[Continued on next page]

(54) Title: IN VIVO IMAGING DEVICE AND METHOD OF MANUFACTURE THEREOF



(57) Abstract: A substantially spherical in vivo imaging device (40) may be used for imaging body lumens in the GI tract. The imaging device (40) may include for example a ballast or weight (74) for setting a preferred orientation of the device within the body lumen. The substantially spherical shape (52) of the in vivo imaging device (40) may facilitate capturing steady streams of imaging data in large body lumens. A method of manufacture is presented.